



1. ELECTRICAL SPECIFICATIONS

Accuracy is indicated as [% rdg + number of dgt] x resolution]. It is referred to 18°C ÷ 28°C with 75%RH

DC Voltage (Autorange)

Range	Resolution	Accuracy	Input impendante	Overload protection
600.0mV	0.01mV	$\pm(1.0\%rdg + 3dgt)$	10M Ω	1000VDC/ACrms
6.000V	0.001V			
60.00V	0.01V			
600.0V	0.1V			
1000V	1V			

AC Voltage TRMS (Autorange)

Range	Resolution	Accuracy	Input impedante	Bandwith	Overload protection
6.000V	0.001V	$\pm(1.0\%rdg + 4dgt)$ (50 ÷ 60Hz) $\pm(3.5\%rdg + 5dgt)$ (61 ÷ 400Hz)	10MΩ	50 ÷ 400Hz	1000VDC/ACrms
60.00V	0.01V				
600.0V	0.1V				
1000V	1V				

Integrated sensor for AC voltage detection: LED turn on for phase-earth voltage > 100V, 50/60Hz

Resistance and Continuity test (Autorange)

Range	Resolution	Accuracy	Buzzer	Overload protection
600.0 Ω	0.1 Ω	$\pm(1.0\%rdg + 5dgt)$	$\leq 50\Omega$	600VDC/ACrms
6.000k Ω	0.001k Ω			
60.00k Ω	0.01k Ω			
600.0k Ω	0.1k Ω			
6.000M Ω	0.001M Ω			
60.00M Ω	0.01M Ω	$\pm(2.0\%rdg + 10dgt)$		

Test current of continuity test: < 0.35mA

AC TRMS Current

Range	Resolution	Accuracy	Bandwith	Overload protection
60.00A	0.01A	±(2.8%rdg + 12dgt)	50 ÷ 60Hz	1000Arms
600.0A	0.1A	±(2.8%rdg + 8dgt)		
1000	1A	±(3.0%rdg + 8dgt)		
60.00A	0.01A	±(4.5%rdg + 10dgt)	61 ÷ 400Hz	
600.0A	0.1A	±(5.0%rdg + 10dgt)		
1000	1A			

PEAK features: response time <10ms



2. GENERAL SPECIFICATIONS

Mechanical characteristics

Size:	252(L) x 88(La) x 51(H)mm
Weight (including battery):	420g
Max conductor size:	45mm

Supply

Battery type:	1 battery 9V NEDA 1604 IEC 6F22 JIS 006P.
Low battery indication:	“+ III” is displayed when the battery level is too low.
Battery life:	about 200 hours
AutoPowerOff:	about 15 minutes of idleness

Display

Characteristics:	4 LCD (max 6000 counts), decimal point, unit symbol indication, bargraph and backlight
Sample rate:	2 times/sec
Conversion mode:	TRMS

Climatic conditions

Reference temperature:	18°C ÷ 28°C
Operating temperature:	5 ÷ 40 °C
Operating humidity:	<80%RH
Storage temperature:	-20 ÷ 60 °C
Storage humidity:	<80%RH

Reference standards

Comply with:	IEC/EN 61010-1
Insulation:	double insulation
Pollution:	Level 2
For inside use, max height:	2000m
Installation category:	CAT IV 600V, CAT III 1000V to the ground

This product conforms to the prescriptions of the European directive on low voltage 2006/95/EEC and to EMC directive 2004/108/EEC