

► Digital-Multimeter

PeakTech® 2015



► SPECIFICATIONS	P 2005
DCV	200 mV/2/20/200/600 V; 100 μ V; +/- 0,5 % + 3 dgt.
ACV	200 mV/2/20/200/600 V; 100 μ V; +/- 0,8 % + 5 dgt. Freq. Bereich: 40 ... 400 Hz
DCA	2/20/200 mA/10 A; 1 μ A; +/- 0,8 % + 3 dgt.
ACA	2/20/200 mA/10 A; 1 μ A; +/- 1,0 % + 5 dgt. Freq.-Bereich: 40 ... 200 Hz
Ohm	200 Ω /2/20/200 k Ω /2/20/2000 M Ω ; 0,1 Ω ; +/- 0,8 % + 3 dgt.
Kapazität / Capacitance	20/200 nF/2/20/200 μ F; 10 pF; +/- 2,5 % + 20 dgt.
Induktivität / Inductance	2/20/200 mH/2/20 H @ 200 Hz; +/- 2,5 % + 20 dgt.
Frequenz / Frequency	2/20/200/2000 kHz/10 MHz; 1 Hz; +/- 1,0 % + 10 dgt.
Temperatur / Temperature	-20 ... +1000°C; 1°C; +/- 1,0 % + 4 dgt.
Betriebsspannung / Operation voltage	9 V-Batterie / Battery
Abmessungen / Dimensions (BxHxT/WxHxD)	95 x 190 x 45 mm
Gewicht / Weight	400 g